

**KEILSTAHL, blankgezogen, DIN 6680**  
**WEDGE STEEL**

Abmessung in mm	kg/m	4301 304	4571 316 TI
2 x 2	0,031	□	□
3 x 3	0,071	○	□
4 x 4	0,126	□	□
5 x 3	0,126	○	□
5 x 5	0,196	□	□
6 x 4	0,188	□	□
6 x 6	0,283	□	□
8 x 5	0,314	□	□
8 x 6	0,453	□	○
8 x 7	0,502	□	□
10 x 5	0,393	○	○
10 x 6	0,471	□	□
10 x 8	0,628	□	□
12 x 6	0,565	○	□
12 x 8	0,754	□	□
12 x 10	0,942	□	□
14 x 6	0,659	□	○
14 x 9	0,976	□	□
16 x 7	0,879	□	□
16 x 10	1,260	□	□
18 x 7	0,988	○	□
18 x 11	1,540	□	□
20 x 8	1,260	○	□
20 x 12	1,880	□	□
22 x 9	1,560	○	□
22 x 14	2,420	□	□
25 x 9	1,730	○	□
25 x 14	2,750	○	□
28 x 10	2,200	○	□
28 x 16	3,520	○	□
32 x 18	4,520	○	□
36 x 20	5,650	○	□
40 x 22	6,950	○	□
45 x 25	8,830	○	□

EDELSTAHL STAINLESS STEEL INOX

□ freibleibender Werksvorrat